



I122KMFH Indirect Fired Multi Fuel Heater



Efficient, versatile and reliable, the I122KMFH portable indirect fired multi fuel heater produces clean, dry, safe heat offering an ideal environment for a variety of special event, emergency, and disaster response applications. The duct-in/duct-out solution uses far less fuel than a single duct-in solution and because the I122KMFH is an "In-direct" fired heater it does not introduce carbon monoxide or moisture into the heated area. The unit burns kerosene, filtered #1 and #2 diesel fuel and JP8 (Jet A Fuel). The unit comes complete with Remote Temperature Controller and Cable (32') and High-Quality PVC Ducting (max length 25'). Unit is available with optional Protective Crash Cage.

TECHNICAL SPECIFICATIONS:

HEATING CAPACITY	122,000 btu/h
HEATING	35.75 kW
CONDITIONED AIR SUPPLY	1060 cfm
DIMENSIONS	49"L X 23"W X 40"H
WEIGHT	167lbs
FUEL TYPES	DF1, DF2, DFA, JP8
FUEL CONSUMPTION	0.86 gal/h
RUNTIME	19.75 hours/tank
FUEL TANK	17 gal or 43.91 liters
DUCT PORTS (2)	14" supply, 14" return
VOLTS/PHASE/HZ	120V/1/60
RUNNING LOAD WATTS	900
RUNNING LOAD AMPS	7.5

TECHNICAL SPECIFICATIONS CONT:

PLUG TYPE	15A STANDARD PLUG
FEATURES,	
	~STAINLESS STEEL BURN CHAMBER
	~AUTO SAFETY CONTROL DEVICES
	~ELECTRONIC FLAME CONTROL
	~POWDER COATED CABINET
	~UL LISTED US/C

