



## 160KRH 205k BTU ELECTRIC HEATER



*Efficient, versatile and reliable, the 160KRH portable electric resistance heater produces clean, dry, safe heat offering an ideal environment for a variety of special event, emergency, disaster or construction applications. The duct-in/duct-out solution adds versatility by allowing you to switch between fan only, 20kw, 40kw and 60kw of heating. The unit comes with unit mounted controls. Power connections are CamLock connectors.*

### PERFORMANCE SPECIFICATIONS:

HEATING CAPACITY	205,000 BTU/H
HEAT RISE FROM AMBIENT	20KW +60 DEG F
	40KW +150 DEG F
	60KW +215 DEG F
MAX OPERATING AMBIENT	75 DEG F ~ 24 DEG C
MIN OPERATING AMBIENT	- 40 DEG F ~ C
SUPPLY AIR – FAN ONLY/20KW	2300 CFM
SUPPLY AIR - 40/60KW	2800CFM
SUPPLY DUCT	18"
RETURN DUCT	16"

### ELECTRICAL SPECIFICATIONS:

VOLTS/PHASE/HZ	<b>208-240V/3PH/60HZ</b>	
MAX POWER DRAW	20KW	RLA 43.1 (17.89KW)
	40KW	RLA 105.2 (42.55KW)
	60KW	RLA 153.3 (62.40KW)
CONNECTION TYPE	CAMLOCKS	
VOLTS/PHASE/HZ	<b>480V/3PH/60HZ</b>	
MAX POWER DRAW	20KW	RLA 29.1 (24.16KW)
	40KW	RLA 52.2 (43.34KW)
	60KW	RLA 75.3 (62.52KW)
CONNECTION TYPE	CAMLOCKS	

