

1425DWH/50 MULTI-FUEL INSTANT WATER HEATER



PERFORMANCE: HEATING CAPACITY **FUEL TYPES** FLOW RATE MAX PRESSURE MIN INLET FLOW RATE

FUEL TANK

ELECTRICAL:

POWER MAX POWER DRAW

POWER CORD

425.000 btu/h DF1, DF2, DFA, JP8 15 gpm 150 psi 1 gpm 10 gal

220V/1PH/50HZ 4 amps

30' w/ EURO PLUG

Efficient and reliable the I425DWH/50 Portable Multi Fuel Fired Water Heater produces a continuous supply of instant hot water. This small footprint unit is compact and durable. The 425,000btu/h water heater comes complete out of the box and ready for field deployment. Features include, Full Instrument Panel, Adjustable Mixing Valve with Anti-Scald Protection, PSI Gauge, Temperature Gauge, Hour Meter, 10 Gal Fuel Tank, two (2) Standard Hot Water Discharge Ports, two (2) Standard Cold Water Supply Ports, one (1) 1.5" Standard Fire Hose Connection Cold Water Supply Port, Switch Burner Protection, High Limit Burner Temperature Shut Off, Dual Lifting Handles, No-Flat Turf Tires and Powder Coated Steel Cover with Stainless Steel Rain Guard. Heater is capable of allweather applications.

CONTROL / INDICATORS:

ON/OFF TOGGLE W/ POWER LIGHT INDICATOR SWITCH. GAUGES W/ COLOR CODED TEMP AND PRESS (PSI). UNIT MOUNTED CONTROLS.

WATER SUPPLY TWO (2) ½" FEMALE NST

ONE (1) 1.5" FIRE HOSE

HOT WATER DISCHARGE TWO (2) MALE CAM LOCK

FITTINGS W/ TETHERED CAPS PORTS 1 – DECON SOLUTION

1 – FRESH RINSE

WEIGHT / DIMENSIONS

398 lbs

46"L x 30"W x 39"H





