

135HC510 PORTABLE AIR CONDITIONER



Expressly designed for worldwide rapid deployment, Isolation Systems 135HC510 Portable HVAC delivers 42,000btu/h cooling and 41,000btu/h heating in one of the easiest to deploy and most versatile 3.5-TON designs on the market.

Unit includes push handles, top mount gear rack, "no flat" turf tire castors, remote or unit mounted controls, 30' power cord with plug end of choice and 2X heavy duty PVC ducts. It is easy to maneuver resulting in a fast setup time by one person. Unit is available in cart mount as pictured, All-Terrain Cart Mount, Trailer Mount or Four Way Fork Liftable Skid design.

TECHNICAL SPECIFICATIONS:

COOLING CAPACITY 42,000 BTU/HR --- POWER DRAW: 15 RLA, 120 LRA

HEATING CAPACITY 41,000 BTU/HR HEAT PUMP --- POWER DRAW: 15 RLA, 120 LRA

RESISTANCE HEATING 5KW or 10KW PRE-INSTALLED CONDITIONED AIR SUPPLY 1400 CFM @ 0.1" WET COIL

REFRIGERANT TYPE R32

DIMENSIONS 56.00"L X 32.00"W X 47.50"H

WEIGHT 489LBS

DUCTS PORTS (2) 12" SUPPLY, 12" RETURN

VOLTAGE 208-240V/1PH/60HZ

HEAT PUMP SINGLE POWER CORD 30AMP CONNECTION
HEAT PUMP + 5KW RH SINGLE POWER CORD 50AMP CONNECTION

HEAT PUMP + 10KW RH DUAL POWER CORDS [1] 30AMP + [1] 50AMP CONNECTION







